

FLOMIX – MV5015/MV6015



MV5015 / MV6015 -Thermostatic Mixing Valve 15mm and 20mm outlet

MV5015 - Standard

MV6015 – NSW Health Care Approved

Features	Benefits
FLOMIX lever, wrist and hand operated taps	
<ul style="list-style-type: none"> ➤ Australia brand ➤ Healthcare compliant product ➤ Anti vandal fixing systems ➤ Isolating valves ➤ Strainers ➤ Double check valves ➤ Flow rates ➤ Hygiene flushing ➤ Temperature adjustment ➤ Point of use tapware ➤ Cleanline design ➤ Easy to maintain ➤ Better whole of life cost benefits ➤ Concentric Adjustable centres ➤ Operating pressures ➤ Operating temperatures ➤ Flow controls ➤ WELS/ Green star ➤ AS4032 ➤ Tested to the highest standards ➤ Laminar flow options ➤ Australian standards ➤ WELS ➤ ISO Approvals ➤ Head office ➤ Warehouse ➤ Custom made products ➤ Product life cycle 	<ul style="list-style-type: none"> - We own the designs, testing, Manufacturing - Australia and international guidelines - Allen key fixing to secure handles - Isolating points with Hot and cold indicators - Removable strainers on the hot and cold side - Prevent hot & cold water cross connection/contamination - Minimum 4lpm Maximum of 54lpm - Intergrated test point for flushing the hot and cold system - Outlet temperature range from 35 – 50deg - Eliminate dead legs reduce the risk of legionella Bacteria - No crevices for Bacteria build up - Cost reduction service and maintenance - Less parts and cheaper components - Easy to install and retrofit adjustable centres - Minimum pressure 50kpa Maximum 1000kpa - Minimum Temperatures 5degree Maximum 85degree - Pressure compensation controller - 3, 4, 5 star rated product - Thermostatic mixing valves code - Performance and materials testing AS4020, AS3718 - Reduction of Bacteria/infection in the air ways - DZR Brass, long lasting & low lead leaching or corrosion - Flow testing to AS6400 - Quality ISO9001 and Green ISO14001 - Sydney CBD Australia - Southern Sydney Australia - Gentec will custom make to suit any application - Life cycle is minimum 15 years, if the product is maintained well the product will outlive 25 years