

GALVANIZED MUNZING RINGS

PRODUCT SPEC SHEET

SPK

SPECIFICATIONS:



Product Code	Wall Thickness	Fits Pipe OD
MRG15	2.0mm	20-23mm
MRG20	2.0mm	24-27mm
MRG25	2.0mm	30-36mm
MRG32	2.0mm	39-46mm
MRG40	2.0mm	45-54mm
MRG50	2.8mm	56-65mm
MRG65	2.8mm	74-82mm
MRG80	2.8mm	85-92mm
MRG100	2.8mm	112-120mm
MRG150	2.8mm	165-175mm

Dacromet® treated steel proven to provide 3 times greater corrosion protection than zinc coating.

M10 boss on all sizes.

WARRANTY

5 Years Warranty

Dacromet® is a surface treatment for applications requiring high levels of protection against corrosion. It comprises of overlapping zinc and aluminum particles in an inorganic binder.

This provides four way corrosion protections:

- **Galvanic Action:** Zinc sacrificially corrodes to protect steel
- **Passivation:** Metal oxides slow down the corrosion reaction of zinc and steel to provide 3 times greater corrosion protection than zinc only
- **Self-Repairing:** Zinc oxides and carbonates migrate to the damaged area of the coating to actively repair the coating and restore barrier protection

SPK

Auckland
Ph: +64 9 271 3720
Address: 49 Sir William Ave, East Tamaki

Christchurch
Ph: +64 3 341 1 271
Address: Unit 5, 4-6 O'Brien's Road, Sockburn

Email: sales@spk.co.nz
Website: <http://www.spk.co.nz>