

# PRODUCT SPEC SHEET

SPK

## AGA GAS BALL VALVES



GBVLFF



GBVTFF



GBVTMF



GBVTF15S

### MATERIAL

Body: Non-DR brass

Handle: Aluminium alloy T/H or Galv. steel L/H

Seal: PTFE

O Ring: NBR

### PERFORMANCE

Working temperature range: 0°C to 80°C

Max working pressure: 1.0 Mpa

Threads: BSP threads on female ends;

Tapered threads on male ends

Performance as per AS4617-2004

### PRODUCT RANGE

Product Code	Description
GBVLFF10	GAS BALL VALVE L/HANDLE F/F 10MM
GBVLFF15	GAS BALL VALVE L/HANDLE F/F 15MM
GBVLFF20	GAS BALL VALVE L/HANDLE F/F 20MM
GBVLFF25	GAS BALL VALVE L/HANDLE F/F 25MM
GBVLFF32	GAS BALL VALVE L/HANDLE F/F 32MM
GBVLFF40	GAS BALL VALVE L/HANDLE F/F 40MM
GBVLFF50	GAS BALL VALVE L/HANDLE F/F 50MM
GBVLFF15L	GAS BALL VALVE L/HANDLE F/F LOCKABLE 15MM
GBVLFF20L	GAS BALL VALVE L/HANDLE F/F LOCKABLE 20MM
GBVTFF15	GAS BALL VALVE T/HANDLE F/F 15MM
GBVTFF20	GAS BALL VALVE T/HANDLE F/F 20MM
GBVTMF15	GAS BALL VALVE T-HANDLE M/F 15MM
GBVTMF20	GAS BALL VALVE T-HANDLE M/F 20MM
GBVTF15S	GAS BALL VALVE T-HANDLE FEMALE - SWIVEL 15MM
GBVTF20S	GAS BALL VALVE T-HANDLE FEMALE - SWIVEL 20MM

### APPROVAL

Certified to AS4617-2004

SPK

Auckland  
Ph: +64 9 271 3720  
Address: 49 Sir William Ave, East Tamaki

Christchurch  
Ph: +64 3 341 1 271  
Address: Unit 5, 4-6 O'Brien's Road, Sockburn

Email: [sales@spk.co.nz](mailto:sales@spk.co.nz)  
Website: <http://www.spk.co.nz>